



TRASFORMATORI STANDARD (230//12V) STANDARD TRANSFORMERS (230//12V)

| Potenza Power | Articolo Article | De x D x H approx. (mm) | Peso (gr) Weight (gr) | Altre caratteristiche Other characteristics |
|------------------|---------------------|----------------------------|--------------------------|--|
| 20 VA | 306015 | 69x15x24 | 390 | |
| | 407010 | 71x25x28 | 470 | |
| | 407010-L | 71x25x28 | 480 | T |
| | 305025 | 58x19x35 | 400 | |
| | 307015 | 77x20x23 | 500 | |
| | 409010 | 96x32x18 | 500 | |
| | GR20 | 85x43x21 | 550 | |
| | 407012 | 73x26x28 | 490 | D |
| | 407012-L | 73x26x28 | 490 | DT |
| | 306017 | 70x15x24 | 395 | D |
| 40 VA | BR135 | 78x26x30 | 590 | |
| | GR40 | 84x32x30 | 590 | |
| | 408010 | 90x26x27 | 620 | |
| 50 VA | AX50 | 80x26x31 | 600 | |
| | AX50-L | 80x26x31 | 600 | T |
| | AX50-IB | 74x23x31 | 550 | |
| | AX50-D | 80x26x31 | 600 | T |
| | AX50-DS | 74x23x31 | 550 | T |
| | 355240 | 60x23x50 | 530 | |
| | AL50 | 61x23x50 | 530 | |
| | 406030-D | 69x28x40 | 550 | T |
| | 5010010-D | 118x38x20 | 840 | DT |
| | 408015-D | 90x26x27 | 650 | DT |
| | 407020 | 80x26x31 | 600 | |
| | 406030 | 69x28x40 | 550 | |
| | 408015 | 90x26x27 | 640 | |
| | 5010010 | 118x38x20 | 840 | |
| | 407022 | 80x26x32 | 620 | DT |
| | 406032 | 70x28x40 | 570 | DT |
| | 5010012 | 118x38x28 | 860 | DT |
| | 407020K | 80x26x32 | 640 | DT |
| | 407023 | 80x26x32 | 620 | D |
| | 406033 | 78x28x40 | 570 | D |
| 5010013 | 118x38x20 | 860 | D | |
| 355243 | 62x22x50 | 550 | D | |
| 408017 | 90x26x27 | 660 | D | |
| 60 VA | AX60 | 90x33x32 | 750 | T |
| | AX60-L | 90x33x32 | 750 | T |
| | 60Z20 | 82x25x33 | 640 | |
| | BR60 | 98x33x32 | 920 | T |
| | 458020 | 90x33x32 | 750 | |
| | 60H20 | 118x37x20 | 850 | |
| | 508020 | 90x35x30 | 850 | |
| 80 VA | AX80 | 98x35x30 | 940 | T |
| | AX80-L | 98x35x30 | 940 | T |
| | 508030 | 90x35x40 | 950 | |
| | 80H40 | 80x35x50 | 900 | |
| 100 VA | AX100-F | 100x37x38 | 1160 | |
| | AX100-T | 100x37x38 | 1160 | T |
| | AX100-L | 100x37x38 | 1160 | T |
| | MO100 | 110x33x25 | 900 | |

T - Protezione termica

Automatic thermal protection

D - Doppia tensione al secondario (9-12V) con commutazione sul primario

Double secondary voltage (9-12V) with primary commutation





TRASFORMATORI STANDARD (230//12V) STANDARD TRANSFORMERS (230//12V)

| Potenza Power | Articolo Article | De x D x H approx. (mm) | Peso (gr) Weight (gr) | Altre caratteristiche Other characteristics |
|------------------|---------------------|----------------------------|--------------------------|--|
| 100 VA | AX1000 | 110x38x36 | 1250 | |
| | AX1000-L | 110x38x36 | 1250 | T |
| | 509020 | 98x35x30 | 970 | |
| | AX101 | 100x37x38 | 1160 | |
| | 651215 | 135x54x25 | 1450 | |
| | 508040 | 91x35x50 | 950 | |
| | 508043 | 91x35x50 | 950 | |
| | 509023 | 99x35x31 | 990 | |
| | AX104 | 100x37x38 | 1170 | |
| 651218 | 136x54x25 | 1480 | | |
| 120 VA | AX120 | 110x38x38 | 1270 | T |
| | AX120-L | 110x38x38 | 1270 | T |
| | 501020 | 110x35x30 | 1100 | |
| | AR 120 | 104x46x48 | 1700 | |
| | AZ120 | 105x45x40 | 1400 | |
| 150 VA | 609530 | 105x45x45 | 1490 | T |
| | 6095 | 105x45x45 | 1490 | T |
| | 6095-L | 105x45x45 | 1490 | T |
| | 609540 | 105x45x50 | 1760 | T |
| | MO150 | 130x38x35 | 1550 | T |
| | MO150-L | 130x38x35 | 1550 | T |
| | 609541 | 105x45x50 | 1760 | |
| | GR150 | 110x40x40 | 1700 | |
| | BR150 | 145x38x30 | 1800 | |
| | RG 150 | 145x38x28 | 1800 | |
| | 609544 | 105x45x50 | 1780 | |
| | 609533 | 105x45x45 | 1480 | |
| | 508630 | 96x35x42 | 1300 | |
| | 200 VA | AX200 | 120x42x40 | 1820 |
| 601130 | | 120x42x40 | 1800 | |
| 601220 | | 130x43x35 | 1930 | |
| MO200 | | 147x45x35 | 1980 | |
| 601133 | | 122x42x40 | 1830 | |
| 250 VA | AX250 | 116x35x49 | 2500 | T |
| | 701140 | 122x55x56 | 2520 | |
| | 601040 | 112x45x55 | 2300 | |
| | MO250 | 145x45x38 | 3050 | |
| 300 VA | AX300 | 125x50x56 | 2640 | T |
| | 701143 | 125x50x56 | 2640 | |
| | 701230 | 135x50x46 | 2700 | |
| 350 VA | CX350 | 126x50x57 | 2660 | T |
| | BX350 | 136x48x47 | 2730 | |
| | AX350 | 127x37x54 | 3460 | |
| 400 VA | AX400 | 144x65x67 | 4130 | T |
| | 801350 | 144x65x67 | 4130 | |
| | 801440 | 154x64x57 | 4200 | |
| | AX400-S | 135x45x65 | 3900 | |
| 450 VA | DX450 | 145x64x68 | 4220 | T |
| 500 VA | AX500 | 145x60x70 | 4300 | T |
| | 801353 | 145x60x70 | 4300 | |
| | AX500-S | 135x45x68 | 4000 | |
| 600 VA | AX600 | 165x60x70 | 5700 | T |
| | 801360 | 165x60x70 | 5700 | |

T - Protezione termica
Automatic thermal protection

D - Doppia tensione al secondario (9-12V) con commutazione sul primario
Double secondary voltage (9-12V) with primary commutation

