



TRASFORMATORI STANDARD (230//12V) STANDARD TRANSFORMERS (230//12V)

Potenza Power	Articolo Article	De x D x H approx. (mm)	Peso (gr) Weight (gr)	Altre caratteristiche Other characteristics
20 VA	306015	69x15x24	390	
	407010	71x25x28	470	
	407010-L	71x25x28	480	T
	305025	58x19x35	400	
	307015	77x20x23	500	
	409010	96x32x18	500	
	GR20	85x43x21	550	
	407012	73x26x28	490	D
	407012-L	73x26x28	490	DT
	306017	70x15x24	395	D
40 VA	BR135	78x26x30	590	
	GR40	84x32x30	590	
	408010	90x26x27	620	
50 VA	AX50	80x26x31	600	
	AX50-L	80x26x31	600	T
	AX50-IB	74x23x31	550	
	AX50-D	80x26x31	600	T
	AX50-DS	74x23x31	550	T
	355240	60x23x50	530	
	AL50	61x23x50	530	
	406030-D	69x28x40	550	T
	5010010-D	118x38x20	840	DT
	408015-D	90x26x27	650	DT
	407020	80x26x31	600	
	406030	69x28x40	550	
	408015	90x26x27	640	
	5010010	118x38x20	840	
	407022	80x26x32	620	DT
	406032	70x28x40	570	DT
	5010012	118x38x28	860	DT
	407020K	80x26x32	640	DT
	407023	80x26x32	620	D
	406033	78x28x40	570	D
5010013	118x38x20	860	D	
355243	62x22x50	550	D	
408017	90x26x27	660	D	
60 VA	AX60	90x33x32	750	T
	AX60-L	90x33x32	750	T
	60Z20	82x25x33	640	
	BR60	98x33x32	920	T
	458020	90x33x32	750	
	60H20	118x37x20	850	
	508020	90x35x30	850	
80 VA	AX80	98x35x30	940	T
	AX80-L	98x35x30	940	T
	508030	90x35x40	950	
	80H40	80x35x50	900	
100 VA	AX100-F	100x37x38	1160	
	AX100-T	100x37x38	1160	T
	AX100-L	100x37x38	1160	T
	MO100	110x33x25	900	

T - Protezione termica

Automatic thermal protection

D - Doppia tensione al secondario (9-12V) con commutazione sul primario

Double secondary voltage (9-12V) with primary commutation





TRASFORMATORI STANDARD (230//12V) STANDARD TRANSFORMERS (230//12V)

Potenza Power	Articolo Article	De x D x H approx. (mm)	Peso (gr) Weight (gr)	Altre caratteristiche Other characteristics
100 VA	AX1000	110x38x36	1250	
	AX1000-L	110x38x36	1250	T
	509020	98x35x30	970	
	AX101	100x37x38	1160	
	651215	135x54x25	1450	
	508040	91x35x50	950	
	508043	91x35x50	950	
	509023	99x35x31	990	
	AX104	100x37x38	1170	
651218	136x54x25	1480		
120 VA	AX120	110x38x38	1270	T
	AX120-L	110x38x38	1270	T
	501020	110x35x30	1100	
	AR 120	104x46x48	1700	
	AZ120	105x45x40	1400	
150 VA	609530	105x45x45	1490	T
	6095	105x45x45	1490	T
	6095-L	105x45x45	1490	T
	609540	105x45x50	1760	T
	MO150	130x38x35	1550	T
	MO150-L	130x38x35	1550	T
	609541	105x45x50	1760	
	GR150	110x40x40	1700	
	BR150	145x38x30	1800	
	RG 150	145x38x28	1800	
	609544	105x45x50	1780	
	609533	105x45x45	1480	
	508630	96x35x42	1300	
	200 VA	AX200	120x42x40	1820
601130		120x42x40	1800	
601220		130x43x35	1930	
MO200		147x45x35	1980	
601133		122x42x40	1830	
250 VA	AX250	116x35x49	2500	T
	701140	122x55x56	2520	
	601040	112x45x55	2300	
	MO250	145x45x38	3050	
300 VA	AX300	125x50x56	2640	T
	701143	125x50x56	2640	
	701230	135x50x46	2700	
350 VA	CX350	126x50x57	2660	T
	BX350	136x48x47	2730	
	AX350	127x37x54	3460	
400 VA	AX400	144x65x67	4130	T
	801350	144x65x67	4130	
	801440	154x64x57	4200	
	AX400-S	135x45x65	3900	
450 VA	DX450	145x64x68	4220	T
500 VA	AX500	145x60x70	4300	T
	801353	145x60x70	4300	
	AX500-S	135x45x68	4000	
600 VA	AX600	165x60x70	5700	T
	801360	165x60x70	5700	

T - Protezione termica
Automatic thermal protection

D - Doppia tensione al secondario (9-12V) con commutazione sul primario
Double secondary voltage (9-12V) with primary commutation

